

OCS Inventory (CentOS 7)

Requisitos

- Apache version 2.2 or higher.
 - Mod_perl version 1.29 or higher.
- PHP 7 or higher, with ZIP and GD support enabled.
 - php_curl
 - php_mbstring
 - php_soap
 - php_xml
- PERL 5.6 or higher.
 - Perl module XML::Simple version 2.12 or higher.
 - Perl module Compress::Zlib version 1.33 or higher.
 - Perl module DBI version 1.40 or higher.
 - Perl module DBD::Mysql version 2.9004 or higher.
 - Perl module Apache::DBI version 0.93 or higher.
 - Perl module Net::IP version 1.21 or higher.
 - Perl module SOAP::Lite version 0.66 or higher (optional)
 - Perl module Mojolicious::Lite
 - Perl module Plack::Handler
 - Perl module Archive::Zip
 - Perl module YAML
 - Perl module XML::Entities
 - Perl module Switch
- MySQL or MariaDB version 4.1.0 or higher with InnoDB engine active. Mysql version upper than 5.5 are not supported but may work.
- Make utility such as GNU make.

Instalando o S.O.

- [CentOS 7](#)

Instalando Dependências

• APACHE

```
yum install -y httpd
systemctl start httpd
systemctl enable httpd
```

• Libera Apache no Firewall interno

```
firewall-cmd --permanent --add-service=http
firewall-cmd --permanent --add-service=https
```

```
firewall-cmd --reload
```

- [Instalar PHP](#)
- Módulos do PHP:

```
yum install -y php-mysqld php-zip php-openssl php-ldap php-gd php-mcrypt php-mbstring php-curl php-xml php-pear php-bcmath php-soap
```

- [MariaDB](#)
- **Perl**

```
yum install -y perl mod_perl
```

- **Perl Modules**

```
yum install -y "perl(XML::Simple)" "perl(Compress::Zlib)"  
"perl(Compress::Zlib)" "perl(DBI)" "perl(Apache::DBI)" "perl(Net::IP)"  
"perl(SOAP::Lite)" "perl(Mojolicious::Lite)" "perl(Plack::Handler)"  
"perl(Archive::Zip)" "perl(YAML)" "perl(XML::Entities)" "perl(Switch)"
```

- **Utilitários de compilação (MAKE)**

```
yum group install -y "Development Tools"
```

Adicionando Repositório

```
wget https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.rpm  
wget --no-check-certificate  
https://rpms.remirepo.net/enterprise/remi-release-7.rpm  
wget --no-check-certificate  
https://rpm.ocsinventory-ng.org/ocsinventory-release-latest.el7.ocs.noarch.r  
pm  
yum install ocsinventory-release-latest.el7.ocs.noarch.rpm epel-release-  
latest-7.noarch.rpm remi-release-7.rpm
```

instalando o OCS

```
yum install yum-utils -y  
yum-config-manager --enable remi  
yum-config-manager --enable remi-php74  
yum install ocsinventory -y
```

Criando base de dados para o OCS

- Entrar no MySQL como root

```
mysql -u root -p
```

- Criar Base:

```
CREATE DATABASE ocs;
```

- Definir **Usuário** e **Senha** para a Base:

```
GRANT ALL PRIVILEGES ON ocs.* TO ocs@localhost IDENTIFIED BY  
"ZVsc&sSE84Si85&x5";
```

Ajustando configurações do PHP

- Editar o arquivo **php.ini** que fica no **/etc/php.ini**

- `vim /etc/php.ini`

- Alterar os valores das linhas **post_max_size** e **upload_max_filesize**
- O mínimo recomendado é 100M mas vamos configurar com folga, para 512M

```
; Maximum allowed size for uploaded files.
```

```
; http://php.net/upload-max-filesize
```

- `upload_max_filesize = 512M`

```
; Maximum size of POST data that PHP will accept.
```

```
; Its value may be 0 to disable the limit. It is ignored if POST data reading  
; is disabled through enable_post_data_reading.
```

```
; http://php.net/post-max-size
```

- `post_max_size = 512M`

- reiniciar o apache após modificação

```
systemctl restart httpd
```

Iniciando configuração do OCS

- Através do navegador acessar o endereço do seu servidor: (Acrescentando: "/ocsreports/")

```
http://192.168.xxx.xxx/ocsreports/
```

- Preencher os dados da Base que foram criados anteriormente

OCS-NG Inventory Installation

WARNING: You will not be able to build any deployment package with size greater than 100MB

You must raise both `post_max_size` and `upload_max_filesize` in your vhost configuration to increase this limit.

WARNING: If you change default database name (ocsweb) or user (ocs), don't forget to update the file 'z-ocsinventory-server.conf' in your Apache configuration directory

MySQL login:	ocs
MySQL password:	
Name of Database:	ocs
MySQL HostName:	localhost
MySQL Port :	3306

Finalizado instalação básica

- Você deverá ver a mensagem de sucesso e as informações de login

Installation finished you can log in index.php with login=admin and password=admin

[Click here to enter OCS-NG GUI](#)

- Com as credenciais: Usuário: admin e senha: admin você já deverá ter acesso à dashboard



All computers

Inventory

Deployment

Configuration

Manage

Extensions

Information

Help



SECURITY ALERT!

Your install.php exists in your installation directory (by default : /usr/share/ocsinventory-reports/ocsreports).

The default login/password is activate on OCS-NG GUI

My dashboard

0

Machine(s)

0

Windows

0

Unix

0

Android

0

Others

0

Operating system

0

Software

Machines contacted today

0

Total

0

Windows

0

Unix

0

Android

From:
<https://gugainfo.com.br/> - **GugaInfo**

Permanent link:
<https://gugainfo.com.br/doku.php?id=tools:ocs>

Last update: **2022/11/03 14:29**



GugaInfo - <https://gugainfo.com.br/>